

Technical Data CMS 730 S knit&wear

Knitting Unit	
Carriages / knitting systems	1 x 3
Combined knitting-transfer systems with variable 2nd stitch tension and motor controlled stitch preparation cams [01]	3 [02]
Electronic wear-free selection systems with 2 selection points	8
Dynamic tension setting with step motors. Extremely quick adjustments of stitch tension with PTS (Power Tension Setting).	●
Manually controlled needle cam exit	●
Presser foot unit	●
Thread insertion with compressed air by means of external air supply	○
Drive / Racking	
Main drive: programmable speed; variable stroke; Power-RCR-System (Rapid Carriage Return); flexible speed adjustment using starting bar; CFC-protection system (Carriage Force Control)	●
Max. knitting speed (m/s) [03]	1,2
Racking: Racking course max. 4", programmable racking speed	●
Needle bed	
Nominal width / max. working width, in inches (cm)	72 (183)
Gauges [04]	E 3,5,2 – 9.2
Gauge conversion	E 3,5,2 – 9.2
Closed spring loaded holding-down jacks with motor control on both needle beds	●
Magnetic thread clamping device	●
Pelrine spring-transfer needle with spring-loaded latch	●
Needle detector	●
Thread clamping and cutting device, independent of carriage, 8 per side [05]	●
Illuminated working space	●
Shock stop motion, front / rear	● ●
Yarn guide	
Yarn control units [06]	24 22 18
Active thread clamp left / right	● ●
Lateral yarn tensioners with scale and following permanent thread brake, on each side	12
Thread deflectors for optimum yarn guidance	●
Yarn feeder rail / yarn feeder	4 14
Intarsia yarn feeder	○
Plating kit consisting of plating yarn feeder and bobbin holder	○
2 additional holders for 4 bobbins each	○
Additional holders for bobbins mounted on the rear side of the machine	○
Yarn feed unit	
Friction feed wheel, 8 tracks each left / right	● ●
Storage feed wheel, max. 2 x 3 [07]	○ [08]
ASCON® – Stitch Calibration System, 8 measurement points, left / right [09]	○
Stoll-multiflex® fabric take-down system	
Main take-down: Tangential method of functioning, adjustable individual roller segments	●
Upper take-down	●
Take-down comb for start of fabric on empty needles	●
Control system / Data processing	
Memory (main computer)	256 MB
Stoll-touchcontrol®: moveable display slide with touchscreen; colour display 800 x 600 pixels	●
2 USB ports; hard-drive; Online via Ethernet	●
Battery back-up: correct continuation of the knitting process after power failure	●
Safety devices	
Fully enclosed working area	●
Machine complies with EC-regulations (CE-mark)	●
Machine status lamp	●
Cleaning device	
Suction device with turbine; with cleaning brush on suction tube	●
Dimensions / Weights	
Length: unpacked in the case on pallet, approx. in mm	3550 3848 3848
Width: unpacked in the case on pallet, approx. in mm	909 1150 1102
Height: unpacked in the case on pallet, approx. in mm	2050 1938 1810
Weight: net gross with case gross with pallet, approx. in kg	1520 2140 1720
Connection value, depending on operating status (kW)	2,7

- Standard equipment
- Special equipment

[01] All systems are fully independent. Knitting with the three-way technique, or simultaneous transfer to the front and rear.

[02] With variable 2nd stitch tension and motor controlled stitch preparation cams.

[03] Depends on yarn and pattern structure.

[04] Gauges E 3,5,2 | 5.2 | 6.2 | 7.2 | 9.2

[05] Independent of carriage.

[06] For gauges E 3,5,2 + 5.2 | 6.2 | 7.2 + 9.2

[07] Requires transformer, not in combination with ASCON®. As standard feature for gauges E9.2

[08] For gauge E 9.2.

[09] System for measuring and regulating the stitch length.

We reserve the right to make technical changes as our products are continuously undergoing further development. All data valid at time of printing 01/12-E.