

## Standard specification:

<b>Control generation:</b>	EKC2 (knitelligence® generation)
<b>Multi-Touch Panel:</b>	Yes
<b>Working width:</b>	36" / 91 cm
<b>Knit and transfer systems:</b>	3 (front/rear)
<b>Distance between systems:</b>	5" (E10-20; E6.2-10.2)
<b>Machine dimensions:</b>	length 2720 mm / depth 1280 mm
<b>Supply voltage:</b>	Flexible voltage connection (AC 230V/400V +/-10%)
<b>Weave-in:</b>	Yes
<b>Yarn guiding:</b>	Direct (from the top)
<b>Yarn carriers:</b>	32 all in one
<b>Yarn control units:</b>	32
<b>Clamp &amp; cutting device:</b>	16 fold left / 16 fold right
<b>Take-down system:</b>	Multiflex + Auxiliary + Comb or Belt with comb
<b>Innovation packages:</b>	<ul style="list-style-type: none"> <li>- Improved central lubrication</li> <li>- Oil drain container</li> <li>- Switch for turning the Belt take-down forwards and backwards</li> <li>- Mirror in the fabric-storage area for Belt take-down machines</li> <li>- Lighting in the fabric-storage area</li> <li>- Can-Open feed wheel interface</li> <li>- Split-stitch without exchanging cams</li> </ul>

## ADF 330



## Options

<b>Gauges:</b>	10; 12; 12/10; 14; 14/12; 16; 18; 18/16; 20; 6.2; 7.2; 8.2; 9.2
<b>Lateral yarn guide:</b>	left / right
<b>ASCON:</b>	- lateral left / right - top left / right
<b>Feed wheels*:</b>	MSF3 / MSF3 (CAN-Open) / EFS 820 ribbon cable / EFS 820 single cable / EFS 820 ribbon cable (CAN-Open) / EFS 920 ribbon cable / EFS 920 single cable / EFS 920 ribbon cable (CAN-Open)
<i>* when selecting storage feed wheels, the friction feed wheels are eliminated</i>	
<b>Light curtain:</b>	vertical support
<b>EVP:</b>	EVP CAN-Open / EVP APM / EVP PPS connector / EVP Crypto tool

## Standard specification:

<b>Control generation:</b>	EKC2 (knitelligence® generation)
<b>Multi-Touch Panel:</b>	Yes
<b>Working width:</b>	84" / 213 cm
<b>Knit and transfer systems:</b>	3 (front/rear)
<b>Distance between systems:</b>	5" (E10-20; E6.2-10.2)
<b>Machine dimensions:</b>	length 3945 mm / depth 1231 mm
<b>Supply voltage:</b>	Flexible voltage connection (AC 230V/400V +/-10%)
<b>Weave-in:</b>	Yes
<b>Yarn guiding:</b>	Direct (from the top)
<b>Yarn carriers:</b>	24 all in one
<b>Yarn control units:</b>	24
<b>Clamp &amp; cutting device:</b>	12 fold left / 12 fold right
<b>Take-down system:</b>	Multiflex + Auxiliary + Comb
<b>Innovation packages:</b>	<ul style="list-style-type: none"> <li>- Improved central lubrication</li> <li>- Oil drain container</li> <li>- Lighting in the fabric-storage area</li> <li>- Can-Open feed wheel interface</li> <li>- Split-stitch without exchanging cams</li> </ul>

## ADF 830



## Options

<b>Gauges:</b>	10; 12; 12/10; 14; 14/12; 16; 18; 18/16; 20; 6.2; 7.2; 8.2; 9.2
<b>Lateral yarn guide:</b>	left / right
<b>ASCON:</b>	- lateral left / right - top left / right
<b>Feed wheels*:</b>	MSF3 / MSF3 (CAN-Open) / EFS 820 ribbon cable / EFS 820 single cable / EFS 820 ribbon cable (CAN-Open) / EFS 920 ribbon cable / EFS 920 single cable / EFS 920 ribbon cable (CAN-Open)
<b>* when selecting storage feed wheels, the friction feed wheels are eliminated</b>	
<b>Light curtain:</b>	vertical support
<b>EVP:</b>	EVP CAN-Open / EVP APM / EVP PPS connector / EVP Crypto tool / EVP Time lock

## Standard specification:

<b>Control generation:</b>	EKC2 (knitelligence® generation)
<b>Multi-Touch Panel:</b>	Yes
<b>Working width:</b>	50" / 127 cm
<b>Knit and transfer systems:</b>	3 (front/rear)
<b>Distance between systems:</b>	5" fine gauges (E10-20; E6.2-10.2) 5,2" coarse gauges (2,5.2-5.2; E5-8)
<b>Machine dimensions:</b>	length 3080 mm / depth 1203 mm
<b>Supply voltage:</b>	Flexible voltage connection (AC 230V/400V +/-10%)
<b>Yarn guiding:</b>	Direct (from the top)
<b>Yarn carriers:</b>	16/24/32 all in one
<b>Yarn control units:</b>	16/24/32
<b>Clamp &amp; cutting device:</b>	8/12/16 fold left / right
<b>Take-down system:</b>	Multiflex + Auxiliary + Comb or Belt with comb
<b>Innovation packages:</b>	<ul style="list-style-type: none"> <li>- Improved central lubrication</li> <li>- Oil drain container</li> <li>- Switch for turning the Belt take-down forwards and backwards</li> <li>- Mirror in the fabric-storage area for Belt take-down machines</li> <li>- Lighting in the fabric-storage area</li> <li>- Can-Open feed wheel interface</li> <li>- Split-stitch without exchanging cams</li> </ul>

## ADF 530



## Options

<b>Weave-in:</b>	Yes (for fine gauges)
<b>Gauges:</b>	<p><b>Fix gauge:</b> E5; 7; 8; 10; 12; 12/10; 14; 14/12; 16; 18; 18/16; 20</p> <p><b>Multi gauge:</b> E2,5.2; 2,5.2(4L); 3,5.2; 3,5.2(4L); 5.2; 6.2; 7.2; 8.2</p>
<b>Lateral yarn guide:</b>	left / right
<b>ASCON:</b>	- lateral left / right - top left / right
<b>Feed wheels*:</b>	MSF3 / MSF3 (CAN-Open) / EFS 820 ribbon cable / EFS 820 single cable / EFS 820 ribbon cable (CAN-Open) / EFS 920 ribbon cable / EFS 920 single cable / EFS 920 ribbon cable (CAN-Open)
<i>* when selecting storage feed wheels, the friction feed wheels are eliminated</i>	
<b>Light curtain:</b>	vertical support
<b>EVP:</b>	CAN-Open / APM / PPS connector / Crypto tool